

Centre feed unit

7

Centre feed units

with double-T and triple-T section busbar



Centre feed unit

Cabinet width	Mounting dimensions	length of the busbar	Cross-section mm ²	Pack size	Weight kg/100 u.	PG	Part no. with link
for cabinet width 600 mm	488 - 563	453	500	1	1434.0	11	35007
for cabinet width 800 mm	688 - 763	653		1	1716.0	11	35006
for cabinet width 600 mm	488 - 563	453	720	1	1716.0	11	35005
for cabinet width 800 mm	688 - 763	653		1	2488.0	11	35004
for cabinet width 600 mm	488 - 563	453	1140	1	2200.0	11	35015
for cabinet width 800 mm	688 - 763	653		1	2940.0	11	35016

Basic system: 2 busbar brackets, 6 mounting brackets with screws, 3 cut-to-length busbars;
4 brackets for covers
for rated currents see product description at www.woehner.com

Universal conductor connection terminal 16 mm² to 300 mm²

For busbar	Connection min. – max.	For use up to max.	Pack size	Weight kg/100 u.	PG	Part no. with link
flat busbars 10 mm and section busbars	16 - 120 mm ² , AWG 6 - 250 MCM	440 A	25	10.9	07	01203
30 x 10 and section busbars	* 95 - 300 mm ²	630 A	3	85.7	07	01094

* see Additional information on aluminium conductor connections Download

Brace terminal for round conductors up to 300 mm²

For busbar	Connection min. – max.	Pack size	Weight kg/100 u.	PG	Part no. with link
20, 25, 30 x 5, 10 and section busbars	* Cu / Al 95 - 185 mm ²	6	31.2	07	01318
20, 25, 30 x 5, 10 and section busbars	* Cu / Al 95 - 300 mm ²	3	42.5	07	01760

* see Additional information on aluminium conductor connections Download

Profile terminal, for double-T section busbars, connection at front and back of busbar section

for the connection of flat busbars and laminated copper busbars

Connection cross-section	Rated current	Centre feed	Terminal space W x H	Pack size	Weight kg/100 u.	PG	Part no. with link
300 - 800 mm ²	1600 A	1600 A	41 x 20 - 42	3	67.0	07	01185
200 - 1200 mm ²			51 x 5 - 28	3	70.5	07	01906
250 - 1512 mm ²			64 x 5 - 28	3	84.0	07	01907
400 - 1000 mm ²		2000 A	51 x 20 - 42	3	73.5	07	01936
500 - 1260 mm ²			64 x 20 - 42	3	85.9	07	01911
630 - 1600 mm ²		2500 A	81 x 20 - 42	3	101.1	07	01934
1120 - 2400 mm ²		2800 A	101 x 20 - 42	3	113.7	07	01935

Profile terminal, for triple-T section busbars, connection at front and back of busbar section

for the connection of flat busbars and laminated copper busbars

Connection cross-section	Rated current	Centre feed	Terminal space W x H	Pack size	Weight kg/100 u.	PG	Part no. with link
420 - 960 mm ²	1600 A	1600 A	41 x 23 - 45	3	105.0	07	01513
350 - 1260 mm ²	2000 A	2500 A	64 x 23 - 45	3	124.0	07	01008
1120 - 2400 mm ²	2500 A	3200 A	101 x 23 - 45	3	172.7	07	01186



Centre feed units

with double-T and triple-T section busbar



Brace terminal, 55 to 105 mm wide, for flat conductors

for the connection of flat busbars and laminated copper busbars

For busbar	Terminal space W x H	Rated current	Centre feed	Pack size	Weight kg/100 u.	PG	Part no. with link
30 x 10 and section busbars	55 x 10 - 28	1600 A	2000 A	3	50.0	07	01069
30 x 10 and section busbars	68 x 10 - 28			3	63.0	07	01070
30 x 10 and section busbars	105 x 10 - 28		2800 A	3	84.0	07	01071

Clip-on screw connection, attachable, for DIN 46234 cable lugs

For busbar	Terminal space W x H	For use up to max.	Pack size	Weight kg/100 u.	PG	Part no. with link
12, 15, 20, 25, 30 x 10 and section busbars	M8 x 8	490 A	20	16.5	07	01514
12, 15, 20, 25, 30 x 10 and section busbars	M10 x 10	630 A	6	36.2	07	01047

Laminated copper busbar, plain, insulated, length 2 m

Dimensions (Number of laminates x width x thickness)	Current at 30 K	Current at 50 K	Cross-section mm ²	Pack size	Weight kg/100 u.	PG	Part no. with link
10x 40 x 1	774 A	1053 A	400	1	746.0	06	01615
10x 50 x 1	914 A	1244 A	500	1	932.0	06	01509
10x 63 x 1	1088 A	1481 A	630	1	1180.0	06	01510
10x 80 x 1	1305 A	1777 A	800	1	1490.0	06	01061
10x 100 x 1	1550 A	2110 A	1000	1	1870.0	06	01273

for additional additional flexible copper busbars see chapter Accessories

Component, for individual mounting

article	used with	Pack size	Weight kg/100 u.	PG	Part no. with link
busbar support, lateral	30 x 10, double-T and triple-T section	2	458.0	11	35008
busbar support, 4-pole, centre	30 x 10, double-T section	1	458.0	11	35009
busbar support, 3-pole, centre	30 x 10, double-T and triple-T section	1	458.0	11	35001
additional cover holder		4	1.4	11	35017

Section busbar, copper

article	Type	Pack size	Weight kg/100 u.	PG	Part no. with link
double-T section busbar 500 mm ²	length 453 mm, tinned	1	200.6	06	01225
double-T section busbar 500 mm ²	length 653 mm, tinned	1	288.1	06	01226
double-T section busbar 720 mm ²	length 453 mm, tinned	1	293.3	06	01838
double-T section busbar 720 mm ²	length 653 mm, tinned	1	424.0	06	01831
triple-T section busbar 1140 mm ²	length 453 mm, tinned	1	464.0	06	01188
triple-T section busbar 1140 mm ²	length 653 mm, tinned	1	672.3	06	01189



Centre feed units

Components for TCC section busbars



Busbar holder, 1-pole

Type	Pack size	Weight kg/100 u.	PG	Part no. with link
for section busbars	6	11.0	06	01369

Section busbar, copper, tin-plated

Type	Width	Pack size	Weight kg/100 u.	PG	Part no. with link
TCC section busbar 1600 mm ²	2400	1	3416.0	06	01610

Connection screw, with nut and spring washer for TCC section busbars

Type	Terminal space W x H	Pack size	Weight kg/100 u.	PG	Part no. with link
hammer-head screw for TCC-profile	M10 x 45	12	5.1	07	01379
bolt for TCC-profile	M12 x 60	12	9.1	07	01380

Brace terminal, 95 to 300 mm², for round conductors

For busbar	Wire range mm ²	For use up to max.	Pack size	Weight kg/100 u.	PG	Part no. with link
20, 25, 30 x 5, 10 and section busbars	* 95 - 185	500 A	6	31.2	07	01318
20, 25, 30 x 5, 10 and section busbars	* 95 - 300	600 A	3	42.5	07	01760

* see Additional information on aluminium conductor connections Download

Brace terminal, 30 to 105 mm wide, for flat conductors

For busbar	Terminal space W x H	Rated current	Centre feed	Pack size	Weight kg/100 u.	PG	Part no. with link
20, 25, 30 x 5, 10 and section busbars	30 x 20	500 A	750 A	6	30.3	07	01319
	32 x 20	550 A	800 A	3	34.7	07	01759
30 x 10 and section busbars	55 x 10 - 28	1600 A	2000 A	3	50.0	07	01069
	68 x 10 - 28			3	63.0	07	01070
	105 x 10 - 28		2800 A	3	84.0	07	01071

